

ITPassLeader

Pass Your Next Certification Exam Fast!

Select a vendor... Select an test... Your email address [Free Download Demo](#)



Instant Download



365 Days Free Updates



Money Back Guarantee



Security & Privacy

Choose the version that fits your needs

PDF Version

Desktop Test Engine

Online Test Engine

Latest and Up-to-Date exam dumps with real exam questions answers.



Get 12-Months free updates without any extra charges.



Experience same exam environment before appearing in the certification exam.



100% exam passing guarantee in the first attempt.



20% discount on more than one license and 30% discount on 5+ license purchases.



100% secure purchase on SSL.



Completely private purchase without sharing your personal info with anyone.



<http://www.itpassleader.com>

High-praise Exam Dumps Questions grant you success by high pass rate - ITPassLeader

Exam : 310-880

Title : SUN Certified Senior System
Support Engineer

Vendors : SUN

Version : DEMO

NO.1 You are updating Jumpstart config files with the following parameters supplied by the customer: system_locale=C timezone=US/Eastern timeserver=129.148.94.5 network_interface=primary {netmask=255.255.255.0 protocol_ipv6=no} terminal=dtterm security_policy=NONE name_service=NONE Which file should you update with the customer required parameters?

- A./etc/bootparams
- B./Jumpstart/rules
- C./Jumpstart/class
- D./Jumpstart/sysidcfg

Correct:D

NO.2 After creating a Jumpstart server, you try to boot the client using the command boot net

-

install, but receive the following messages: ok boot net - install Boot device:

/pci@1f,700000/network@2 File and args: - install Timeout waiting for ARP/RARP packet
Timeout

waiting for ARP/RARP packet Timeout waiting for ARP/RARP packet Timeout waiting for
ARP/RARP packet Timeout waiting for ARP/RARP packet Timeout waiting for ARP/RARP
packet

Which five could cause this problem? (Choose five.)

- A.Alias "net" not correctly set
- B.Client not running watch-net-all
- C.in.rarpd not running on boot server
- D.Network cable not correctly connected
- E.A duplicate hostname in /etc/hosts
- F.Failed to issue a reconfigure boot command
- G.MAC address entry missing in /etc/ethers

Correct:A C D E G

NO.3 You install a system to customer specifications and after rebooting you get the following

message: NIS server not responding for ... retrying The customer tells you that there is a network

problem which prevents this machine from reaching the NIS server. You boot the machine into

single user mode. What action should you take to allow the system to operate until the NIS server

is reachable again?

- A. Edit `/etc/nsswitch.conf` so that file is first for all entries and reboot into multiuser mode.
- B. Copy `/etc/nsswitch.files` to `/etc/nsswitch.conf` and reboot into multiuser mode.
- C. Edit `/etc/resolv.conf` so that the domain entry is commented out and reboot into multiuser mode.
- D. Rename `/etc/rc2.d/S72inetsvc` to `/etc/rc2.d/DisabledS72inetsvc` and reboot into multiuser mode.

Correct: B

NO.4 A user of DHCP is having trouble connecting to a DHCP server. After analyzing the system, you find the DHCP daemon is NOT running. Which command should you use to start the DHCP daemon?

- A. `/usr/lib/inet/dhcppd`
- B. `/etc/rc2.d/dhcp start`
- C. `/etc/init.d/dhcp start`
- D. `/etc/init.d/S45dhcp start`
- E. `/etc/rc2.d/S99dhcpageant start`

Correct: C

NO.5 A customer has centralized platform and domain logging on a Sun Fire 6800 to a log server called 'sfv210-a'. The customer wants to keep the platform and domain messages separate, so

they have configured the System Controller on the Sun Fire 6800 to use the syslog facility 'local0' for the platform messages, and 'local1' for the domain messages. What two lines should be added

to the `/etc/syslog.conf` file on the log server 'sfv210-a' to separate the two types of syslog messages? (Choose two.)

- A. `local0.notice /var/adm/messages`
- B. `local1.notice /var/adm/messages`
- C. `local1.notice /var/adm/messages.local1`
- D. `local0.notice /var/adm/messages.local0`
- E. `local0.notice sfv210-a:/var/adm/messages.local0`
- F. `local1.notice sfv210-a:/var/adm/messages.local1`

Correct: C D

NO.6 You are installing a Sun Fire E2900 on a customer site and the customer wants to

configure the

POST level on the System Controller to run at the maximum level. What command from the LOM

prompt should you run to configure the SC POST level?

A.setupsc

B.setuplom

C.setupnetwork

D.setupplatform

Correct:A

NO.7 A customer is connected to a remote machine and needs to know some information about the

CPUs installed. Which two Solaris commands can be used to determine the number of CPUs installed, and the speed of each? (Choose two.)

A.psradm

B.cputat

C.devfsadm

D.psrinfo -v

E.prtdiag -v

Correct:D E

NO.8 You are conducting a pre-install site survey for 8 Sun Fire V890s and 4 Sun Rack 900s in a raised

floor environment. The customer wants to install them in 2 rows, one in front of the other. How

should you configure the placement of the systems?

A.The Sun Fire V890s should be placed back to back, and perforated floor tiles should be placed in front of the racks.

B.The Sun Fire V890s should be placed back to back, and perforated floor tiles should be placed at the rear of the racks.

C.The Sun Fire V890s should be facing the same direction, one behind the other, and perforated floor tiles should be placed in front of the racks.

D.The Sun Fire V890s should be facing the same direction, one behind the other, and perforated floor tiles should be placed both in front of, and at the rear of the racks.

Correct:A

NO.9 You are checking a Sun Fire V880 system configuration for dual-loop fibre disk operation. What command will show the existence of dual-loop?

- A.prtfru -v
- B.prtconf -pv
- C.prtdiag -v
- D.luxadm display enclosure
- E.luxadm -e disp_port_map path_to_disk

Correct:D

NO.10 You are configuring the eri0 network interface using the ifconfig command with the options netmask + and subnet mask 255.255.255.0. # /usr/sbin/ifconfig eri0 netmask + To verify the system is properly set up you issue an ifconfig -a command. You notice that the eri0 network interface has the netmask incorrectly set for 255.255.0.0. Which file do you need to check first?

- A./etc/hosts
- B./etc/netmasks
- C./etc/hostname.eri0
- D./etc/nsswitch.conf

Correct:B

NO.11 You are asked to configure a Sun Fire 6800 domain to remotely mount /usr/local. The filesystem mount must have the following properties: 1) The client must not be able to delete files on the server. 2) The filesystem must be automatically mounted at boot time. Which /etc/vfstab entry meets both requirements?

- A.remote-server:/usr/local - /usr/local nfs - no rw
- B.remote-server:/usr/local - /usr/local nfs - yes ro
- C.remote-server:/usr/local - /export/local nfs - no rw
- D.remote-server:/export/local - /usr/local rfs - yes ro

Correct:B

NO.12 A customer wants a new PCI Ethernet card installed in a Sun Fire E2900. After physically

installing the card, you want to verify that the system recognizes the card before the OS is booted.

Which two OBP commands can you use to accomplish this? (Choose two.)

- A.devalias
- B.show-devs
- C.show-nets
- D..inet-addr
- E.probe-net-all
- F.probe-scsi-all

Correct:B C

NO.13 You are installing a 66 Mhz PCI card in a Sun Fire 6800. The customer tells you they want the

best performance from the card. (Note, the customer has no PCI+ I/O Boards installed in the system) How many slots in an 8-slot PCI I/O Board can operate at 66 Mhz?

- A.0
- B.1
- C.2
- D.3
- E.4

Correct:C

NO.14 You receive a call from a customer who states that their Solaris 9 NTP client is not synchronizing

to their NTP server. Which three commands should you use to investigate further? (Choose three.)

- A.ntpq -p
- B.svcs -l xntp
- C.ps -ef | grep xntp
- D.cat /etc/inetd/ntp.client
- E.cat /etc/inetd/ntp.server
- F.grep xntpd /var/adm/messages

Correct:A C F

NO.15 You have connected a workstation's 'ce0' interface into a network with a DHCP service. Which

command should you issue to have your workstation receive a DCHP IP address from the server?

- A.dhcp get ce0
 - B.dhcpconfig ce0
 - C.ifconfig ce0 plumb dhcp
 - D.ifconfig ce0 plumb auto-dhcp
- Correct:D

NO.16 You are installing a Sun Fire 15K server. The System Controller comes with a pre-installed, EIS

compliant Solaris image. You need to confirm that this image was installed with the current EIS

CD. Which file can be used to determine the current version of the EIS CD used on a system?

- A./etc/motd
- B./etc/release
- C./sun/install.log
- D.\$SMSETC/SMS/config/smsversion.cf

Correct:C

NO.17 You begin to boot a Sun Fire V1280 server, but realize some additional settings need to be

checked. You decide to stop the boot and bring the system to the OK prompt. How can you accomplish this during the boot process?

- A.Type ~..
- B.Type break.
- C.Go to the lom > prompt and type break.
- D.Go to the lom > prompt and type reset -x.

Correct:C

NO.18 You have performed a setkeyswitch on for domain A on a Sun Fire 6800 where the auto-boot?

OBP variable is set to false. What command at the OBP should you run to find the status of the

POST?

- A.showlog-results
- B.showlog results
- C.show-log-results
- D.showpost-results
- E.showpost results

F.show-post-results

Correct:F

NO.19 You are installing a used StorEdge 3310 SCSI array on a Sun Fire V480 server. You want to determine if the disks have updated firmware. Which command should you use to evaluate the firmware level?

A.fru stat

B.iostat -En

C.iostat -tcx

D.prtconf -pv

E.luxadm -e probe | grep version

F.luxadm display -v /dev/rdisk/cXtXdX

Correct:B

NO.20 A customer requires additional swap space on their system. As the customer does not want to repartition their disks, a decision to use a swap file is made. Which entry should you use in the /etc/vfstab file so that the new swap file is activated automatically when the system is booted?

A./path/filename - - swap - no -

B./path/filename - - tmpfs - no -

C./path/filename - - swap - yes -

D./path/filename - - tmpfs - yes -

Correct:A